

WINTECH



225 Series Aluminum Hung

CPD #	U-factor	SHGC	VT	Condensation Resistance	Low-E	Gap Widths	Spacer	Overall Glass Thickness	GapFill	Label Number
WNT-A-6-00001-00001	0.64	0.69	0.7	18	# 2	0.438	Polycarb	7/16	AIR (100%)	547
WNT-A-6-00002-00001	0.49	0.24	0.41	18	# 3	0.438	Polycarb	7/16	AIR (100%)	548
WNT-A-6-00003-00001	0.49	0.36	0.41	18	# 2	0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00004-00001	0.5	0.26	0.47	18	# 2 & # 3	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00005-00001	0.48	0.21	0.24	18		0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00006-00001	0.65	0.55	0.52	18	# 3	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00007-00001	0.5	0.36	0.47	18	# 2	0.438	Polycarb	3/8	AIR (100%)	
WNT-A-6-00008-00001	0.5	0.24	0.34	18	# 2 & # 3	0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00009-00001	0.49	0.21	0.17	18		0.438	Polycarb	7/16	AIR (100%)	
WNT-A-6-00010-00001	0.65	0.68	0.7	18		0.375	Polycarb	3/8	AIR (100%)	
WNT-A-6-00011-00001	0.65	0.53	0.48	18	# 3	0.375	Polycarb	3/8	AIR (100%)	
WNT-A-6-00012-00001	0.5	0.28	0.32	18	# 3	0.375	Polycarb	3/8	AIR (100%)	

547

 National Fenestration Rating Council® CERTIFIED		WinTech Window Technology, Inc. 225 Aluminum Frame Double Glazing - Air Fill Product Type: Vertical Slider CPD# WNT-A-6-00001-00001	
ENERGY PERFORMANCE RATINGS			
U-Factor (U.S./I-P)		Solar Heat Gain Coefficient	
.64		.69	
ADDITIONAL PERFORMANCE RATINGS			
Visible Transmittance			
.70			
<small>Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product energy performance. NFRC ratings are determined for a fixed set of environmental conditions and specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. www.nfrc.org. Consult manufacturers literature for other performance information.</small>			
Glazing - 5/8" SSB x Air x SSB Clear Glazing complies with ASTM E 1300. Glazing complies with ASTM E 330-10 as tested. Winload Structural Performance Tested: 50 PSF Tested in accordance to AAMA/WDMA/CSA 101/I.S. 2/A440 -05 and AAMA/WDMA/CSA 101/I.S. 2/A440 -08			

548

 National Fenestration Rating Council® CERTIFIED		WinTech Window Technology, Inc. 225 Aluminum Frame Double Glazing - Air Fill - Low E Product Type: Vertical Slider CPD# WNT-A-6-00002-00001	
ENERGY PERFORMANCE RATINGS			
U-Factor (U.S./I-P)		Solar Heat Gain Coefficient	
.49		.24	
ADDITIONAL PERFORMANCE RATINGS			
Visible Transmittance			
.41			
<small>Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product energy performance. NFRC ratings are determined for a fixed set of environmental conditions and specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. www.nfrc.org. Consult manufacturers literature for other performance information.</small>			
Glazing - 5/8" SSB Low E (#2) x Air x SSB Clear Glazing complies with ASTM E 1300. Glazing complies with ASTM E 330-10 as tested. Winload Structural Performance Tested: 50 PSF Tested in accordance to AAMA/WDMA/CSA 101/I.S. 2/A440 -05 and AAMA/WDMA/CSA 101/I.S. 2/A440 -08			

225 Series Slider