



## WinTech Access Doors Minimum WIDTH Sizes

Latest Rev. 9-9-11 KB

### Minimum Door Opening Width Sizes (Day Light Door Width in Inches)

Hardware	Interference Clearance Condition	1 1/2" 1g T / NT	2" 1g T / NT	2" 2g T / NT	4" 1g T / NT	4" 2g T / NT
<b>No Hardware</b>	Standard	8	16	10	12	14
	Tight	5	11	7.5	10.5	10.5
<b>Allegis: WinTech supplied configuration</b>	Standard	11	16	11	19	18
	Tight	9.5	11	10	19	18
<b>Allegis Prep Only: Using industry std config</b>	Standard	11	16	11	19	18
	Tight	9.5	11	10	19	18
<b>VentLok 260</b>	Standard	9	16	10	n/a	n/a
	Tight	8.5	11	8	n/a	n/a
<b>VentLok 310</b>	Standard	n/a	n/a	n/a	12	14
	Tight	n/a	n/a	n/a	11	12
<b>VentLok 350</b>	Standard	12	16	11	18	14
	Tight	11	15	10	17	13

**Standard:** 1/16" gap clearance before any swing interference assuming perfect manufacturing, assembly and installation.

**Tight:** No clearance gap at the tightest interference point assuming perfect manufacturing, assembly and installation. The door will click due to contact when opened/closed.

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION INTENDED FOR THE PRIVATE USE OF WINTECH AND ITS CUSTOMERS. ©2010 Window Technology, Inc. (dba WinTech) ALL RIGHTS RESERVED.