

3200 Family

3200 Window Performance

Series / Configuration	AAMA Rating	Air	Water	Standard U Value	Optional U Value with Foam
3220 - Fixed Center Set	CW-PG60	0.03	12 psf	0.34	N/A
3220 - FX/PO/FX/PI	CW-PG60	0.01	12 psf	0.47	N/A
3220 - COL-FX-COR	CW-PG60	0.01	12 psf	0.52	
3250 - Fixed	CW-PG50	0.01	10 psf	0.32	0.29
**3210 - Slider	CW-PG50	0.03	7.5 psf	0.37	0.35
**3270 - Double Hung	CW-PG50	0.085	7.5 psf	0.41	0.39
**3260 - Single Hung	CW-PG50	0.085	7.5 psf	0.38	0.35

**Double Thermal Break Framing

3200 Hardware Charts

Series / Configuration	Cam Locks	Pole Ring Cam Locks	Roto Operators	4 Bar Arms	Butt Hinges	Limit Stops
3220 - Projected & Casement	S	O	N/A	S	N/A	O

Series / Configuration	Sweep Locks	S/S Rollers	Limit Stops
3210 - Slider	S	S	O

Series / Configuration	Sweep Locks	Block and Tackle Balances	Limit Stops	Auto Sill Lock	Auto Head Lock
3260 - Single Hung 3270 - Double Hung	S	S	O	O	O

S - Standard O - Optional N/A - Not Available

Glazing Options

Open Glazed By Others, 1/4" Monolithic to 1" Insulated on All Windows

* No Open Glazing on SH and DH Units

Finish Options

AAMA 2604 Paints & Class 1 Clear and Color Anodizing

Standard colors and additional options on back

AAMA 2605 paint options available

Accessories Options

Subframe, Panning, Interior Trim, Perimeter Nail Fins, 3 Piece Mullions, Trans-Mullions, Vinyl Frame Filler, F Anchors

325 Family

325 Window Performance

Series / Configuration	AAMA Rating	Air	Water	Standard U Value	Optional U Value with Foam
320 - Project Out	CW-PG80	0.01	12 psf	0.53	N/A
320 - Project In	CW-PG80	0.03	12 psf	0.54	N/A
320 - Casement Out	CW-PG80	0.03	12 psf	0.52	N/A
320 - Casement In	CW-PG80	0.01	12 psf	0.52	N/A
350 - Fixed	CW-PG80	0.01	12 psf	0.36	N/A
310 - Slider	CW-PG60	0.06	10 psf	0.44	N/A
370 - Double Hung	CW-PG50	0.1	10 psf	0.44	N/A

325 Hardware Charts

Series / Configuration	Cam Locks	Pole Ring Cam Locks	Roto Operators	4 Bar Arms	Butt Hinges	Limit Stops
320 - Projected	S	O	O	S	O	O

Series / Configuration	Sweep Locks	S/S Rollers	Limit Stops
310 - Slider	S	S	O

Series / Configuration	Sweep Locks	Block and Tackle Balances	Limit Stops	Auto Sill Lock	Auto Head Lock
370 - Double Hung	S	S	O	O	O

S - Standard O - Optional N/A - Not Available

Glazing Options

Open Glazed By Others, 1/4" Monolithic to 1" Insulated on operable windows. Up to 1 7/8" glass thickness on fixed windows

** No Open Glazing on SH and DH Units*

Finish Options

AAMA 2604 Paints & Class 1 Clear and Color Anodizing

Standard colors and additional options on back

AAMA 2605 paint options available

Accessories Options

Subframe, Panning, Interior Trim, Perimeter Nail Fins, 3 Piece Mullions, Trans-Mullions, Vinyl Frame Filler, F Anchors