










2560/260 SERIES DATA SHEET

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft ² -°F)	CR	STC/ OITC*
								
Single Hung	LC-PG35-H	44 x 75	35	5.43	<0.10	0.43	29	29/24

**Performance varies based on glass selection, contact WinTech for project specific performance. U-Factor based on 5/8" IGU with soft-coat low-e and argon.*

WinTech's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.

STANDARD FEATURES:

- Material: Aluminum
- Frame Depth: 2-7/16"
- Typical Wall Thickness: 0.55"
- Standard Infill Options: 5/8" & 1/4"
- Min Size:
 - 16" x 23"
- Max Size:
 - 44" x 75"

ACCESSORIES:

- Subframe/ receptor system
- Panning
- Interior Trim
- Mullions

SPECIFICATIONS:

- AAMA/WDMA/CSA/101/I.S.2/A440 (NAFS)
- AAMA 1503
- AAMA 2604 & 2605
- ASTM E90
- ASTM E1332



CONFIGURATIONS:

