

## G/M225 SERIES DATA SHEET

| Type                                                                             | FGIA/ AAMA<br>RATING                                                              | Test Size<br>(in.)                                                                | Design<br>Pressure<br>(psf)                                                       | Water<br>(psf)                                                                    | Air<br>(cfm/sf<br>@1.57 psf)                                                       | U-Factor*<br>(btu/h-ft <sup>2</sup> -°F)                                            | CR                                                                                  | STC/<br>OITC*                                                                       |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |  |  |
| Single Hung                                                                      | LC-PG50-H                                                                         | 44 x 75                                                                           | 50                                                                                | 7.52                                                                              | <0.30                                                                              | 0.46                                                                                | 19                                                                                  | n/a                                                                                 |

*\*Performance varies based on glass selection, contact WinTech for project specific performance. U-Factor based on 5/8" IGU with soft-coat low-e and argon.*

*WinTech's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.*

### STANDARD FEATURES:

- Material: Aluminum
- Frame Depth: 2-1/4"
- Typical Wall Thickness: 0.55"
- Standard Infill Options: 5/8" IG
- Min Size:
  - 16" x 23"
- Max Size:
  - 44" x 75"
- Integral Nail Fin
- Finish Options:
  - Mill
  - Bronze
  - White

### SPECIFICATIONS:

- AAMA/WDMA/CSA/101/I.S.2/A440 (NAFS)
- AAMA 1503
- AAMA 2603
- NFRC 100/200/500
- ASTM E90
- ASTM E1332



### CONFIGURATIONS:

