WINTECH
An Employee Owned Company

G/M225

Single Hung Tilt
2-1/4" Frame Depth

G/M225 Series data sheet

Type	FGIA/ AAMA RATING	Test Size (in.)	Design Pressure (psf)	Water (psf)	Air (cfm/sf @1.57 psf)	U-Factor* (btu/h-ft2-°F)	CR	STC/ OITC*
Single Hung	LC-PG30-H	44 x 75	30	7.52	<0.30	0.46	19	n/a

***Performance varies based on glass selection, contact WinTech for project specific performance. U-Factor based on 5/8" IGU with soft-coat low-e and argon.**

***WinTech's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.**

Standard Features:

- *Material: Aluminum*
- *Frame Depth: 2-1/4"*
- *Typical Wall Thickness: 0.55"*
- *Standard Infill Options: 5/8" IG*
- *Min Size:*
  - *16" x 23"*
- *Max Size:*
  - *44" x 75"*
- *Integral Nail Fin*
- *Finish Options:*
  - *Mill*
  - *Bronze*
  - *White*



Specifications:

- *AAMA/WDMA/CSA/101/I.S.2/A440 (NAFS)*
- *AAMA 1503*
- *AAMA 2603*
- *NFRC 100/200/500*
- *ASTM E90*
- *ASTM E1332*

Configurations:

