


## OZARKVIEW SERIES DATA SHEET

| Type                                                                              | FGIA/ AAMA<br>RATING                                                              | Test Size<br>(in.)                                                                | Design<br>Pressure<br>(psf)                                                       | Water<br>(psf)                                                                    | Air<br>(cfm/sf<br>@1.57 psf)                                                       | U-Factor*<br>(btu/h-ft <sup>2</sup> -°F)                                            | CR<br>or CRF                                                                        | STC/<br>OITC*                                                                       |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |  |  |  |  |
| Single Hung                                                                       | R-PG50-H                                                                          | 44 x 75                                                                           | 50                                                                                | 7.5                                                                               | <0.08                                                                              | 0.29                                                                                | 61                                                                                  | n/a                                                                                 |

*\*Performance varies based on glass selection, contact WinTech for project specific performance. U-Factor based on 3/4" IGU with soft-coat low-e and argon.*

*WinTech's products are tested and certified in a controlled laboratory environment. Field performance will vary due to installation methods, environmental conditions, and product configuration.*

### STANDARD FEATURES:

- Material: Vinyl
- Frame Depth: 3-1/4"
- Typical Wall Thickness: 0.62"
- Standard Infill Options: 3/4"
- Min Size:
  - 18" x 31"
- Max Size:
  - 44" x 75"
- Std. Hardware
  - Sweep Lock
  - Coil Balances

### COLOR OPTIONS:

| Exterior | Interior |
|----------|----------|
| White    | White    |
| Tan      | Tan      |
| Black    |          |

### SPECIFICATIONS:

- AAMA/WDMA/CSA/101/I.S.2/A440 (NAFS)
- AAMA 1503
- AAMA 2604 & 2605
- NFRC 100/200/500
- ASTM E90
- ASTM E1332



### CONFIGURATIONS:

